EXPOSURE SCENARIO REPORT			cms.helpdesk@alcumus.com
ID#:	3406633	Assessment Owner:	Clive Owen
Fax:	01189794328	Phone:	07712556825
Email:	clive@a1groupuk.com	Date Created:	13/10/2017 13:40:00
Date Assessment Reviewed	23/02/2023	Next Review Date:	23/02/2028 11:54:00
Material Code:	156112	Tradename:	GREENOX, ADBLUE, AUTOMOTIVE UREA SOLN
		Supplier	TENNANTS DISTRIBUTION LIMITED
Supplier Phone:	0161 205 4454	IMC:	
Keyword	Fuel (Additive)	Frequency of use:	Weekly
Approximately how much of the material is used by one person in one working day:	10 LITRES	How many people are directly exposed?:	1
Are any other people put at risk from indirect exposure?:	No	How are they exposed?:	
Are there any susceptible workers?:	No	Susceptible Categories:	
Other info:		Is this material being used outside of the normal temperature range?:	No
Additional work practices:			
Existing Control measures:			
Exp Limit			
Notes	Greenox <sup>®</sup> , AdBlue <sup>®</sup> , Automotive Urea Solutio	on, AUS, Diesel Exhaust Fluid, DEF	
Files Uploaded			
File Name			
Activities			
Act NoMethod1Pouring	Area Outside	Exposure Up to 1/2 hour per shift	
Work Area Work Area Code WW	Sub Area Code		
Safer Substitute Chosen Reason for	leaving/swapping material		

SUMMARY SHEET		ID# 3406633		cms.helpdesk@alcumus.com
FACILITY A1 GROUP	MAIN	WW	SUB	IMC 156112
Material/Process GREENOX, ADBLUE,	AUTOMOTIVE UREA			ested in quantity Considerations titis may result from prolonged contact
LOW HAZARD			May cause eye irritation	
LIQUID		•		
SupplierTENNANTS DISTRKeywordFuel (Additive)ContentsUrea: 32.5%	-	al Word Limit		

Method Pouring	А	rea Outside		Exposure Up to	o 1/2 hour per shift	Spillage Ventilate area
LOV	V ACUTE RISK - FULL EXI	POSURE	LO	W CHRONIC RISK - FUL	L EXPOSURE	Wear polythene or nitrile gloves
ontrol Measures	LOW	ACUTE RISK - INDIVIDUA		LOW CH		Wear eye protection if contact likely Wear respiratory protection for large spills in poorly ventilated areas Wear protective overalls and footwear for large spillages Absorb in sand or inert absorbent material
		$\bigcirc$				Small spills - wipe up with cloth Collect into a container, close lid Dispose or recycle of spillages in a controlled manner - Refer to Hazardous Waste Regulations if approp First Aid
AVOID SKIN CONTACT	POLYTHENE OR NITRILE	IF CONTACT LIKELY		WASH AFTER EXPOSURE	IF HEAVILY SOILED	Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill Ingestion - do not induce vomiting, wash out mouth with water If feeling unwell consult your doctor immediately Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor
	Î					Fire Isolated small scale fire: Water - state of the provider - form - isort material



23/02/2023

Date Printed 23/02/2023



CLOSE ALL

CONTAINERS

CONTROLLED

STORE /WASTE

Water - carbon dioxide - powder - foam - inert material Large fire: evacuate area, call fire brigade or follow site procedure Wear self-contained breathing apparatus and protective clothing



#### **Health Hazards**

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact May cause eye irritation



This assessment was compiled by Alcumus Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

Date Printed 23/02/2023



Date Assessment Reviewed

23/02/2023

Latest Safety Data Sheet Reference

20/05/2015

CONTROL SHEET			
REQUEST DETAILS	#ID:	3406633	User making request Clive Owen
MATERIAL DETAILS	Material Code:	156112	LOW UNCONTROLLED ACUTE RISK
Tradename:	GREENOX, ADBLUE, AUTO	OMOTIVE UREA SOLN	LOW UNCONTROLLED CHRONIC RISK
			LOW CONTROLLED ACUTE/CHRONIC RISK
IMC		Supplier	TENNANTS DISTRIBUTION LIMITED
ACTIVITY DETAILS			
Act No Method 1 Pouring	Area Outside	Exposure	2 hour per shift
		Op to 1/2	
SCENARIO DETAILS	Additional work practices:		
Approximately how much of the r used by one person in one workin		Frequency of use: Weekly	How many people are directly exposed?: 1
Are any other people put at risk fr exposure?:	from indirect No		
Are there any susceptible workers	No	Susceptible	e Categories:
Work Area Code WW		Sub Area Code	
Other Information			
Greenox <sup>®</sup> , AdBlue <sup>®</sup> , Automotive Ure	ea Solution, AUS, Diesel Exha	ust Fluid, DEF	
Considerations			Answer



### PRODUCT: GREENOX® (ADBLUE®) (ADBL) REVISION: 5 DATED: 20/05/15 PAGE 1 OF 6 PRODUCT SPECIFICATION

	PRODUC		AIION	
Product Name	Greenox® (AdB			
Alternative Name			32, diesel exhaust flu	id, DEF
Specification Reference	ADBL/5 (05/15/			
	SALES	SPECIFICAT	ION	
Characteristics	Unit	Min	Max	Typical Value
Urea Content	Weight %	31.8	33.2	32.5
Density	g/cm <sup>3</sup>	1.087	1.093	1.0895
Refractive Index at 20°C		1.3814	1.3843	1.3829
Alkalinity as NH <sup>3</sup>	%	-	0.2	
Biuret	%	-	0.3	
Aldehydes	mg/kg	-	5	
Insolubles	mg/kg	-	20	
Phosphate (PO <sub>4</sub> )	mg/kg	-	0.5	
Calcium	mg/kg	-	0.5	
Iron	mg/kg	-	0.5	
Copper	mg/kg	-	0.2	
Zinc	mg/kg	-	0.2	
Chromium	mg/kg	-	0.2	
Nickel	mg/kg	-	0.2	
Aluminium	mg/kg	-	0.5	
Magnesium	mg/kg	-	0.5	
Sodium	mg/kg	-	0.5	
Potassium	mg/kg	-	0.5	
Greenox® conforms to DIN '	70070 and ISO 2224	l and is supplied rea	ady to use.	
Storage				
To maintain the product qual				
Do not store or allow product	t to come into contac	t with mild steel, alu	uminium, brass, copp	er or alloys. These will
lamage the catalyst system.				
Shelf Life (in accordance with				
Constant ambient storage t	emperature (°C)	Minimum shelf life	e (months)	
≤10		36		
<u>≤25</u>		18		
≤ <u>30</u>		12		
≤35		6		2
		Significant	decomposition test b	before use
≥35				
Freezing	4 1100 11 1		4 1°4 - 4	TTI 1''' 1 1 0
Freezing Adblue® will begin to freeze				
<b>Freezing</b> Adblue® will begin to freeze partially frozen solution will	still be at the require			
Freezing Adblue® will begin to freeze	still be at the require			

### **Exclusion of Liability**

Information contained in this publication is accurate to the best of the knowledge and belief of Tennants.

Any information or advice obtained from Tennants otherwise than by means of this publication and whether relating to Tennants materials or other materials, is also given in good faith. However, it remains at all times the responsibility of the customer to ensure that Tennants materials are suitable for the particular purpose intended.

Tennants accepts no liability whatsoever (except as otherwise provided by law) arising out of the use of information supplied, the application, adaptation or processing of the products described herein, the use of other materials in lieu of Tennants materials or the use of Tennants materials in conjunction with such other materials.

#### Health and Safety

A Material Safety Data Sheet has been issued describing the health, safety and environmental properties of this product, identifying the potential hazards and giving advice on the handling precautions and emergency procedures. This must be consulted fully before handling, storage and use.



### PRODUCT: GREENOX® (ADBLUE®) (ADBL) REVISION: 5 DATED: 20/05/15 PAGE 2 OF 6 SAFETY DATA SHEET

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

#### **1.1 Product Identifier** Trade Name

CAS Number

Composition

2.

**EINECS** Number

Greenox®, AdBlue®, Automotive Urea Solution, AUS, Diesel Exhaust Fluid, DEF 57-13-6 200-315-3 01-2119463277-33-xxxx (Urea) Mixture of urea and water

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s):  $NO_x$  reducing agent, for injection into exhaust system of diesel engines. Industrial use for flue gas  $NO_x$  reduction.

Uses advised against: None

**REACH Registration Number** 

#### 1.3 Details of the supplier of the safety data sheet

Tennants Distribution Limited Hazelbottom Road Cheetham Manchester M8 0GR Tel: 44(0)161 205 4454 Fax: 44(0) 161 203 4298 Email: msds@tennantsdistribution.com

#### **1.4 Emergency telephone number**

Tel: 44(0)844 335 0001 (24 hours)

### HAZARDS IDENTIFICATION

#### 2.1 Classification of substance or mixture

According to Regulation (EC) No. 1272/2008 (CLP). This product is not classified according to the CLP regulation.

#### Classification according to Directive 67/548/EEC or Directive 1999/45/EC Not classified

#### Information concerning particular hazards for human health and environment:

See section 16 for full text of any R phrases or H statements above see section 11 for more details on any health effects or symptoms.

2.2 Label elements Labelling according to Regulation (EC) 1272/2008: None Hazard pictograms: None Signal word: None Hazard statements: None

2.3 Other hazards Results of PBT and vPvB assessment PBT: Not applicable

vPvB: Not applicable

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Chemical characterisation:** Mixture **CAS No.:** 57-13-6 **Description:** Urea **Identification Numbers:** 

EC Number: 200-315-5

Chemical characterisation: Mixtures

Description: An aqueous solution of urea

**Dangerous components:** There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

### PRODUCT: GREENOX® (ADBLUE®) (ADBL) REVISION: 5 DATED: 20/05/15 PAGE 3 OF 6 FIRST AID MEASURES

# 4.

#### 4.1 Description of first aid measures General advice: No special measures required.

## Inhalation

Avoid inhalation of vapour mist or spray. If inhaled, supply fresh air. Get medical attention in case of complaints. Skin contact

Immediately rinse with water. If skin irritation continues, get medical attention.

### **Eve contact**

Check for and remove any contact lenses. Rinse opened eye for several minutes under running water. Get medical attention if irritation occurs.

Ingestion

Rinse out mouth and then drink plenty of water. Do not induce vomiting: call for medical help immediately.

**Protection of first-aiders** 

## No action shall be taken involving any personal risk or without suitable training.

### 4.2 Most import symptoms and effects, both acute and delayed

Potential acute health effects:

Eve contact: No known significant effects or critical hazards.

Inhalation: Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin contact: No known significant effects or critical hazards.

Ingestion: No known significant effects or critical hazards.

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

#### FIRE FIGHTING MEASURES 5.

### 5.1 Extinguishing Media

Suitable extinguishing media: Use fire extinguishing methods suitable to surrounding conditions.

Unsuitable extinguishing media: Not known

### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture: In a fire or if heated, a pressure increase will occur and the container may burst. Hazardous thermal decomposition products: Decomposition products may include the following materials carbon dioxide, carbon monoxide, nitrogen oxides and ammonia. Avoid breathing dusts, vapours or fumes from burning materials. In case of inhalation of decomposition products in a fire, symptoms may be delayed.

### 5.3 Advice for fire-fighters

Special precautions for fire fighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire fighters: Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

#### ACCIDENTAL RELEASE MEASURES 6.

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

Do not allow to enter sewers/surface or ground water.

### 6.3 Methods and material for containment and cleaning up

Absorb with liquid binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable receptacles.

### 6.4 Reference to other sections

No dangerous substances are released. See section 7 for information on safe handling. See section 8 for information on personal protection equipment. See section 13 for disposal information.



<b>PRODUCT: GREENOX®</b>	(ADBLUE®) (ADBL) REVISION: 5 DATED: 20/05/15 PAGE 4 OF 6
7. HANDLING AND ST	
7.1 Precautions for safe handling	
Prevent formation of aerosols. Ensure go	bod ventilation in the workplace.
Technical measures/ Precautions: Store	in a closed, dry room with good ventilation at temperature not below -11 $^{\circ}$ C
and not above +30 °C. Instructions on th	e limit quantity of the substance/preparation to be stored under the conditions
specified: no.	
Information about fire and explosion pro	
7.2 Conditions for safe storage, include	ling any incompatibilities
Storage:	
	tore away from oxidising agents. See section 10. Protect from frost, store in
cool, dry conditions in well-sealed recep	tacles.
7.3 Specific end use(s)	
	<sup>9</sup> C to keep product in best condition. For use in catalytic SCR systems the
	nto contact at any point with: mild steel, aluminium, brass or copper as these
will poison the catalyst.	
	S/PERSONAL PROTECTION
	f technical facilities: No further data, see section 7.
8.1 Control Parameters	monitoring at the workplace
Ingredients with limit values that require	
workplace.	ant quantities of materials with critical values that have to be monitored at the
8.2 Exposure controls	
Personal protective equipment:	s taking place into account the product properties.
General protective and hygiene measu	
	e skin. Do not eat, drink, smoke or sniff while working. Avoid contact with the
	sols. Wash hands before breaks and at the end of work.
Eye/face protection	
Safety glasses.	
Hand protection	
Wear gloves impermeable to the produc	t.
Respiratory protection	
In case of inadequate ventilation wear re	spiratory protection. Recommended: Filter P2 (EN143)
Body protection	
Protective work clothing.	
9. PHYSICAL AND CHEN	IICAL PROPERTIES
9.1 Information on basic physical and c	hemical properties
Appearance	Fluid
Colour	Clear
Odour	Ammonia like or odourless
pH-value at 20°C	8-10
Melting point (°C)	-11°C
Boiling point (°C)	
Decomposition temperature	Not determined
Self-igniting	Product is not self-igniting
Danger of explosion	Product does not present an explosion hazard
Flash point	Not applicable
Flammability	Not flammable
Explosion limits	Not determined
Vapour pressure at 20°C	23 hPa
Density at 20°C	$1.087 \text{ to } 1.093 \text{ g/cm}^3$
Solubility in/miscibility with water	Fully miscible
Partition coefficient (n-octanol/water)	Not determined. Inorganic substance.
Viscosity	1.4 mPa.s @20°C



PRODUCT: GREENOX® (ADBLUE®) (ADBL) REVISION: 5 DATED: 20/05/15 PAGE 5 OF 6
10. STABILITY AND REACTIVITY
10.1 Reactivity
Stable under regular conditions.
10.2 Chemical stability
Stable under regular conditions.
Thermal decomposition/conditions to be avoided
The residue upon evaporation decomposes on heating above 220°C producing toxic gases.
10.3 Possibility of hazardous reactions
Reacts violently with strong oxidants, nitrates, inorganic chlorides, chlorites and perchlorates causing fire and
explosion hazard.
10.4 Conditions to avoid
For intended use, avoid contamination with metal, dust or organic matter.
10.5 Incompatible materials
Strong oxidising agents, nitrate, chlorites and perchlorates. For intended use, the product must not be in contact with
mild steel, aluminium, brass, copper or alloys as these can damage the catalyst system.
10.6 Hazardous decomposition products
Under normal conditions none.
11. TOXICOLOGICAL INFORMATION
11.1 Information on toxicological effects
Acute toxicity
Acute oral toxicity: LD50: 8471 mg/kg bw (for urea).
Acute dermal toxicity: LD50: 8200 mg/kg bw (for urea).
Acute inhalation toxicity: not relevant.
Skin irritation or/and sensitization: Not irritating. Not sensitizing effect known.
Mutagenicity: Ames-test: negative
Carcinogenicity: Ames-test: negative
Reproductive toxicity: Ames-test: negative
Specific toxicity for particular organ (STOT) (one time effect): None.
Specific toxicity for particular organ (STOT) (repeated effect): None.
12. ECOLOGICAL INFORMATION
12.1 Toxicity
Aquatic toxicity
57-13-6 Urea
EC50 >10000 mg/kg (daphnia)
12.2 Persistence and degradability
Biodegradable
<b>12.3 Bioaccumulative potential</b> Product is not expected to bioaccumulate
12.4 Mobility in soil
No further relevant information available
12.5 Results of PBT and vPvB
PBT: Not applicable
vPvB: Not applicable
12.6 Other adverse effects
No further relevant information available.
13. DISPOSAL CONSIDERATIONS
13.1 Waste treatment methods
Recommendation
Recommended Hierarchy of Controls:
Minimise waste
Reuse if not contaminated
Recycle, e.g. dilution and use as fertilizer
Safe disposal (if all else fails).
European waste catalogue Waste code 06 10 99 (wastes not otherwise specified)
13.2 Uncleaned packaging
Recommendation: Disposal must be made according to official regulations
Recommended cleansing agents: Water if necessary together with cleansing agents

S

TENNANTS DISTRIBUTION LIMITED HAZELBOTTOM ROAD, CHEETHAM, MANCHESTER M8 0GR TEL 44(0)161 205 4454 FAX 44(0)161 203 4298

<b>PRODUCT: GREENOX® (ADBLUE®)</b> (ADBL) REVISION: 5 DATED: 20/05/15 PAGE 6 OF 6
14. TRANSPORT INFORMATION
This product is not classed as hazardous for transport (ADR, RID, IMDG).
15. REGULATORY INFORMATION
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization Substances of
very high concern: Not applicable.
Other EU regulations
Europe inventory: All components are listed or exempted.
Seveso II Directive
This product is not controlled under the Seveso II Directive. National regulations
Notes: To our knowledge no other country or state specific regulations are applicable.
15.2 Chemical safety assessment: A chemical safety assessment has not been carried out.
16. OTHER INFORMATION
Abbreviations
EC50: median effective concentration
LC50: median lethal concentration
LD50: median lethal dose
NOEC: no observable effect concentration
OEL: occupational exposure limit
PBT: persistent, bioaccumulative, toxic chemical
PNEC: predicted no-effect concentration
STEL: short-term exposure limit
TWA: time weighted average
vPvB: very persistent, very bioaccumulative chemical
Source of key data used to compile the data sheet
Supplier information
Modifications from last revision
The Specification has been updated. The Safety Data Sheets have been revised in accordance with current
requirements
<b>Date:</b> 20/05/15
Copyright <sup>©</sup> Tennants Distribution Ltd (2015)

The attached supplier's/distributor's Safety Data Sheet (SDS) is made available for internal reference use only; it is not to be redistributed outside of your organisation without the express permission of the supplier or distributor. The attached SDS remains the intellectual property of, and all rights are reserved to the original compilers. Alcumus Sypol Limited makes no warranty either expressed or implied as to the suitability or accuracy of the attached SDS; it is the latest version of the SDS as made available to Alcumus Sypol Limited and may not always reflect the latest version(s) available direct from the supplier or distributor of the material described within the SDS. The use of any information within the attached SDS is at the sole discretion, risk and responsibility of yourselves as subscribers to the Sypol CMS database. No representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by Alcumus Sypol Limited or by its officers, employees or agents in relation to the adequacy, accuracy, completeness or reasonableness of the attached SDS. All and any such responsibility and liability is expressly disclaimed to the extent permitted by law. While Alcumus Sypol Limited used the information within the attached SDS to compile the associated assessment, the classification used by Alcumus Sypol Limited to compile the assessment may differ from the classification assigned to the supplier or distributor if it is appropriate to do so under the classification requirements of any relevant domestic or international law to which the supplier or distributor is subject.