ID#:	80913	**User making request:**	Clive Owen
Fax:	01189794328	**Phone:**	07712556825
Email:	clive@a1groupuk.com	**Date Created:**	16/03/2011
Date Assessment Reviewed	16/10/2017	**Next Review Date:**	16/10/2022
Material Code:	4939	**Tradename:**	DUCAL SUPER & DUCAL ENGINE OIL
Supplier Code:	8088	**Supplier:**	CBOC LUBRICANTS
Supplier Phone:	0117 9412159	**IMC:**	
Keyword:	Oil (Mineral)	**Frequency of use:**	Daily
Approximately how much of the material is used by one person in one working day:	1 gallon	**How many people are directly exposed?:**	1
Are any other people put at risk from indirect exposure?:	No	**How are they exposed?:**	
Are there any susceptible workers?:	No	**Susceptible Categories:**	
Other info:		**Is this material being used outside of the normal temperature range?:**	No
Additional work practices:			
Existing Control measures:	gloves worn		
Exp Limit	5mg/m3 15mSTEL,10mg/m3 8hrTWA oil		
Notes			

Files Uploaded

File Name

Activities

Act No.	Method	Area	Exposure
2	Pouring	Outside	Up to 1/2 hour per shift

Work Area

Work Area Code	Sub Area Code
CS	

Safer Substitute Chosen No **Reason for leaving/swapping material** preferred supplier

FACILITY A1 GROUP **MAIN** CS **SUB** 4939

MATERIAL/PROCESS

DUCAL SUPER & DUCAL ENGINE OIL

MEDIUM HAZARD

LIQUID

SUPPLIER CBOC LUBRICANTS
KEYWORD Oil (Mineral)

CONTENTS

Not classified as hazardous under the CLP regulations: 100%,
Highly refined mineral oils, multifunctional additives

SIGNAL WORD NONE
EXP LIMIT 5mg/m3 15mSTEL,10mg/m3 8hrTWA oil

HEALTH HAZARDS

May cause ill health if ingested in quantity
May cause eye irritation
Skin - irritation and dermatitis may result from prolonged contact
Mechanically degraded mineral oil may cause skin cancer
When using do not eat, drink or smoke

CONSIDERATIONS

METHOD Pouring **AREA** Outside **EXPOSURE TIME** Up to 1/2 hour per shift

LOW RISK - FULL EXPOSURE

LOW RISK - INDIVIDUAL ACTIVITY

CONTROL MEASURES

KEEP SKIN COVERED

NITRILE

IF SPLASH LIKELY

WASH AFTER CONTACT

IF SOILED

SPILLAGE

Ventilate area
Do not allow uncontrolled spillages to enter mains drain/sewers/water courses
Wear nitrile gloves
Wear eye protection if splash likely
Wear protective clothing if whole container is spilt
Absorb in sand or inert absorbent material
Collect into a container, close lid
Dispose or recycle of spillages in a controlled manner

FIRST AID

Inhalation - remove to fresh air and rest
After a significant exposure or if feeling unwell call for medical assistance immediately
Ingestion - do not induce vomiting
Ingestion - give plenty of water in sips
If feeling unwell consult your doctor immediately
Eye - irrigate with water for at least 15 minutes
Skin - wash with soap/cleanser and rinse with water
If irritation persists then consult a doctor

FIRE

Isolated small scale fire:
Powder - foam - carbon dioxide (CO2)
Large fire: evacuate area, call fire brigade or follow site procedure
Wear self-contained breathing apparatus and protective clothing
Toxic fumes are produced when material is involved in a fire

Alcumus Your Trusted Partner

ACTIVITY COMMENTS

This assessment was compiled by Alcumus Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

Printed 06/03/2018

A1 Wokingham group

FACILITY A1 GROUP **MAIN** CS **SUB** 4939

MATERIAL/PROCESS

DUCAL SUPER & DUCAL ENGINE OIL

SUPPLIER CBOC LUBRICANTS
KEYWORD Oil (Mineral)
SIGNAL WORD NONE

MEDIUM HAZARD

LIQUID

METHOD Pouring **AREA** Outside **EXPOSURE TIME** Up to 1/2 hour per shift **ACTIVITY COMMENTS**

LOW RISK - FULL EXPOSURE

LOW RISK - INDIVIDUAL ACTIVITY

CONTROL MEASURES

KEEP SKIN COVERED

NITRILE

IF SPLASH LIKELY

WASH AFTER CONTACT

IF SOILED

HEALTH HAZARDS

May cause ill health if ingested in quantity
May cause eye irritation
Skin - irritation and dermatitis may result from prolonged contact
Mechanically degraded mineral oil may cause skin cancer
When using do not eat, drink or smoke

Alcumus® Your Trusted Partner

This worker sheet was compiled by Alcumus Sypol Limited from the full COSHH assessment. Refer to the full assessment for further information regarding all aspects of safe use. For advice call the helpdesk on 01296 678464

Printed 06/03/2018

Wokingham A1 group

REQUEST DETAILS #ID: 80913 User making request: Clive Owen

MATERIAL DETAILS Material Code: 4939

LOW UNCONTROLLED RISK

Tradename: DUCAL SUPER & DUCAL ENGINE OIL

LOW CONTROLLED RISK

IMC: Supplier: CBOC LUBRICANTS

ACTIVITY DETAILS

Act No.	Method	Area	Exposure
2	Pouring	Outside	Up to 1/2 hour per shift

SCENARIO DETAILS Additional work practices:

Approximately how much of the material is used by one person in one working day:	1 gallon	Frequency of use:	Daily	How many people are directly exposed?:	1
Are any other people put at risk from indirect exposure?:	No	How are they exposed?:			
Are there any susceptible workers?:	No	Susceptible Categories:			

WORK AREA

Work Area Code	Sub Area Code
CS	

CONSIDERATIONS		Answer
	Has the elimination or substitution of this material been considered?	YES
	Have users been informed, instructed and trained in the use of the relevant COSHH control measures?	YES
	Are procedures to ensure the maintenance of controls in place?	YES
	Are procedures to undertake skin checks in place?	YES
	Are specific records in accordance with the COSHH Regulations suitably maintained?	YES

REG 13

Have all actions to be taken in the event of an emergency been considered? YES