

ID#:	80713	Assessment Owner:	Clive Owen
Fax:	01189794328	Phone:	07712556825
Email:	clive@a1groupuk.com	Date Created:	10/03/2011 11:24:00
Date Assessment Reviewed	23/02/2023	Next Review Date:	23/02/2028 11:55:00
Material Code:	175597	Tradename:	FIXT SILICONE SPRAY LUBE.
		Supplier	FIXT UK
Supplier Phone:	02476 322 196	IMC:	
Keyword	Lubricant (Aerosol)	Frequency of use:	Daily
Approximately how much of the material is used by one person in one working day:	few squirts	How many people are directly exposed?:	2-5
Are any other people put at risk from indirect exposure?:	No	How are they exposed?:	
Are there any susceptible workers?:	No	Susceptible Categories:	
Other info:		Is this material being used outside of the normal temperature range?:	No

Additional work practices:**Existing Control measures:**

gloves and goggles

Exp Limit

N-hexane 72mg/m3 8hTWA 20ppm 8hTWA WEL, Petroleum gases, liquefied 1750mg/m3 8hTWA 2180mg/m3 15mSTEL

Notes

Classification is based upon the contents stated in the supplier's safety data sheet rather than upon the supplier's classification.

Files Uploaded**File Name****Activities**

Act No	Method	Area	Exposure
1	Spraying (Aerosol)	Outside	Up to 1/2 hour per shift

Work Area**Work Area Code**

CS

Sub Area Code**Safer Substitute Chosen****Reason for leaving/swapping material** maintain same supplier

Material/Process
FIXT SILICONE SPRAY LUBE.

MEDIUM HAZARD

AEROSOL

Supplier FIXT UK
Keyword Lubricant (Aerosol)

Contents
 Petroleum gases, liquefied: 60 - 100%, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane: 10 - 30%, N-hexane: < 1%

Signal Word Danger
Exp Limit N-hexane 72mg/m3 8hTWA 20ppm 8hTWA WEL, Petroleum gases, liquefied 1750mg/m3 8hTWA 2180mg/m3 15mSTEL



Health Hazards
 Extremely flammable aerosol
 Pressurised container: May burst if heated.
 Causes skin irritation
 Potential for ototoxic effects that may cause hearing loss
 May cause drowsiness or dizziness
 Toxic to aquatic life with long lasting effects
 May cause ill health if ingested in quantity
 May cause eye irritation



Method	Area	Exposure
Spraying (Aerosol)	Outside	Up to 1/2 hour per shift
LOW ACUTE RISK - FULL EXPOSURE		LOW CHRONIC RISK - FULL EXPOSURE

Control Measures	Area	Exposure
	Outside	Up to 1/2 hour per shift
	LOW ACUTE RISK - INDIVIDUAL ACTIVITY	LOW CHRONIC RISK



KEEP SKIN COVERED NITRILE OR VITON IF CONTACT LIKELY WASH AFTER EXPOSURE IF SOILED



PRESSURISED

Spillage
 Not applicable when intact
 In case of leakage or loss of containment:
 Ventilate area and exclude all sources of ignition
 Wear protective clothing if whole container is spilt
 Allow to dissipate
 Wear nitrile or viton gloves
 Ensure area is safe before re-entry

First Aid
 Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill
 Ingestion - do not induce vomiting, wash out mouth with water
 If feeling unwell consult your doctor immediately
 Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor
 Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire
 Keep aerosol cans cool, do not burn for disposal
 Isolated small scale fire:
 Vapour may spread - distant ignition is possible
 Water fog - carbon dioxide - powder - foam
 Do not use water jet
 Large fire: evacuate area, call fire brigade or follow site procedure
 Wear self-contained breathing apparatus and protective clothing
 Keep containers cool with water spray
 Risk of explosion if involved in a fire



Activity Comments
 Intermittent use of aerosol spray.

Date Printed 23/02/2023



Material/Process
FIXT SILICONE SPRAY LUBE.

MEDIUM HAZARD
AEROSOL



Supplier FIXT UK
Keyword Lubricant (Aerosol)
Signal Word Danger

Method Spraying (Aerosol) **Area** Outside **Exposure** Up to 1/2 hour per shift **Activity Comments** Intermittent use of aerosol spray.

LOW ACUTE RISK - FULL EXPOSURE **LOW CHRONIC RISK - FULL EXPOSURE**

LOW ACUTE RISK - INDIVIDUAL ACTIVITY **LOW CHRONIC RISK**

Control Measures



KEEP SKIN COVERED



NITRILE OR VITON



IF CONTACT LIKELY



WASH AFTER EXPOSURE



IF SOILED



PRESSURISED

Health Hazards
 Extremely flammable aerosol
 Pressurised container: May burst if heated.
 Causes skin irritation
 Potential for ototoxic effects that may cause hearing loss
 May cause drowsiness or dizziness
 Toxic to aquatic life with long lasting effects
 May cause ill health if ingested in quantity
 May cause eye irritation



This assessment was compiled by Alcumus Sygol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

Date Printed 23/02/2023



REQUEST DETAILS #ID: 80713 User making request: Clive Owen

MATERIAL DETAILS Material Code: 175597

Tradename: FIXT SILICONE SPRAY LUBE.

LOW UNCONTROLLED ACUTE RISK

LOW UNCONTROLLED CHRONIC RISK

LOW CONTROLLED ACUTE/CHRONIC RISK

IMC Supplier: FIXT UK

ACTIVITY DETAILS

Act No	Method	Area	Exposure
1	Spraying (Aerosol)	Outside	Up to 1/2 hour per shift

SCENARIO DETAILS Additional work practices:

Approximately how much of the material is used by one person in one working day: few squirts Frequency of use: Daily How many people are directly exposed?: 2-5

Are any other people put at risk from indirect exposure?: No

Are there any susceptible workers?: No Susceptible Categories:

Work Area Code Sub Area Code

CS

Other Information

Classification is based upon the contents stated in the supplier's safety data sheet rather than upon the supplier's classification.

Considerations

Answer



Has the elimination or substitution of this material been considered?

Yes



Have you implemented the use of the engineering controls before resorting to the use of RPE?

Yes



Are all personnel provided with necessary RPE, suitably trained in its correct use, maintenance, and storage and been fit tested where required?

Yes



Are procedures to ensure the maintenance of controls in place?

Yes



Are procedures to conduct exposure monitoring in place?

Yes



Are procedures to undertake urine tests in place?

No

All actions to be taken in the event of an emergency have been considered

SYPOL

Dear Subscriber,

This front sheet has been attached to the Safety Data Sheet (SDS) as an indication that it does not meet the current requirements of Article 31 of REACH (Registration, Evaluation, Authorisation and restriction of Chemicals) which governs the content of a SDS, the equivalent UK REACH legislation or similar international legislation comparable with Annex 4 of the United Nations Globally Harmonized System (GHS). The SDS may refer to obsolete hazard classification systems or predate the implementation of current legislative systems.

As this is the latest version of the SDS made available to Alcumus no warranty either expressed or implied is given as to the suitability or accuracy of its content, therefore the use of any information within the SDS is at the sole discretion and responsibility of yourselves as subscribers to the Alcumus COSHH database.

While Alcumus used the information within the attached SDS to compile the associated COSHH assessment, the classification used by Alcumus to compile the assessment may differ from the classification assigned by the supplier or distributor if it is appropriate to do so under the classification requirements of relevant European Directives and UK national legislation.

It is strongly advised that you contact the supplier/manufacturer of the material to obtain a revised copy of the SDS that conforms to the appropriate standards.

Should you require any more information, please contact the CMS helpdesk on **+44 (0)1296 678464**, or at CMS.helpdesk@alcumusgroup.com

Discover more at **0330 127 7526**
or **www.alcumus.com**



SAFETY DATA SHEET

FIXT Silicone Spray Lube

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name FIXT Silicone Spray Lube

Product number FX081125

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Lubricant aerosol

1.3. Details of the supplier of the safety data sheet

Supplier Seymour Road
Nuneaton
Warwickshire
CV11 4LB

02476 322 196 (T)
02476 322 117 (F)
info@fixtconsumables.com

1.4. Emergency telephone number

Emergency telephone 02476 322 196

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Aerosol 1 - H222, H229

Health hazards Skin Irrit. 2 - H315

Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) F+;R12. R52/53,R67.


Human health Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

Environmental This product contains substances which are very toxic or toxic to aquatic organisms and may cause long term effects to the aquatic environment (see sections 2 and 12)

Physicochemical Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

2.2. Label elements

Pictogram



Signal word Danger

FIXT Silicone Spray Lube

Hazard statements	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated H412 Harmful to aquatic life with long lasting effects. H315 Causes skin irritation.
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P102 Keep out of reach of children. P260 Do not breathe vapour/spray. P271 Use only outdoors or in a well-ventilated area. P501 Dispose of contents/container in accordance with local regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS		60-100%
CAS number: 68476-85-7	EC number: 270-704-2	
Classification Flam. Gas 1 - H220 Press. Gas, Liquefied - H280	Classification (67/548/EEC or 1999/45/EC) F+;R12 Carc. Cat. 1;R45 Muta. Cat. 2;R46	
HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		10-30%
CAS number: —	EC number: 921-024-6	REACH registration number: 01-2119475514-35
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Asp. Tox. 1 - H304 STOT SE 3 - H336 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Xn;R65. Xi;R38. F;R11. N;R51/53. R67.	
HEXANE-norm		<1%
CAS number: 110-54-3	EC number: 203-777-6	REACH registration number: 01-2119480412-44
Classification Flam. Liq. 2 - H225 STOT RE 2 - H373 Skin Irrit. 2 - H315 Repr. 2 - H361f STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) F;R11 Repr. Cat. 3;R62 Xn;R48/20,R65 Xi;R38 R67 N;R51/53	

FIXT Silicone Spray Lube

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once.
Inhalation	If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
-------------------------------------	--

5.2. Special hazards arising from the substance or mixture

Specific hazards	Extremely flammable. Forms explosive mixtures with air. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure build-up.
-------------------------	---

5.3. Advice for firefighters

Protective actions during firefighting	Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved.
---	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours.
-----------------------------	--

6.2. Environmental precautions

Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion.
--------------------------------	--

FIXT Silicone Spray Lube

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Do not spray on a naked flame or any incandescent material.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Extremely flammable. Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Long-term exposure limit (8-hour TWA): WEL 1200 mg/m³

HEXANE-norm

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m³

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Appropriate engineering controls Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.

Personal protection When using do not smoke.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber). The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Hygiene measures Wash hands after handling. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

FIXT Silicone Spray Lube

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Clear.
Odour	Organic solvents.
Initial boiling point and range	-40 to -2°C @ 1013 hPa
Flash point	<-40°C
Upper/lower flammability or explosive limits	Lower : 1.8% - Upper 9.5%
Vapour pressure	ca. 590 to 1760 kPa @ 45°C
Vapour density	ca. 1.5 at 15°C
Partition coefficient	log Pow: ca. 2.3 to 2.8
Auto-ignition temperature	410-580°C
Comments	Information given is applicable to the major ingredient.

9.2. Other information

Other information	Not available.
Volatile organic compound	This product contains a maximum VOC content of 560 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Stable at normal ambient temperatures and when used as recommended.
-------------------	---

10.2. Chemical stability

Stability	Avoid the following conditions: Heat, sparks, flames.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Does not decompose when used and stored as recommended.
---	---

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.
----------------------------	--

10.5. Incompatible materials

Materials to avoid	Keep away from oxidising materials, heat and flames.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours.
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General information	Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.
----------------------------	---

FIXT Silicone Spray Lube

Inhalation	In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Unconsciousness, possibly death.
Skin contact	Irritating to skin.
Eye contact	Vapour or spray in the eyes may cause irritation and smarting.
Acute and chronic health hazards	Arrhythmia (deviation from normal heart beat). Irritating to skin. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
Route of entry	Inhalation
Target organs	Central nervous system Respiratory system, lungs
Medical symptoms	Skin irritation. Arrhythmia (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness.

SECTION 12: Ecological Information

Ecotoxicity	This product has not been tested but contains ingredients which are toxic or very toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment. During normal use the volatility of the components and the packaging form, pressurised container, make entry into the aquatic environment unlikely, however, do not empty or discharge into drains or watercourses. Ensure container is empty before disposal to prevent contents entering watercourses.
--------------------	---

12.1. Toxicity

Toxicity	Not available.
-----------------	----------------

12.2. Persistence and degradability

Persistence and degradability	Not available.
--------------------------------------	----------------

12.3. Bioaccumulative potential

Bioaccumulative potential	Not available.
----------------------------------	----------------

Partition coefficient	log Pow: ca. 2.3 to 2.8
------------------------------	-------------------------

12.4. Mobility in soil

Mobility	Not known.
-----------------	------------

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	Not available.
---	----------------

12.6. Other adverse effects

Other adverse effects	Not available.
------------------------------	----------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Do not puncture or incinerate, even when empty.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated because of the risk of an explosion.

SECTION 14: Transport information

FIXT Silicone Spray Lube

General

This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following.

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS	F-D, S-U
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

FIXT Silicone Spray Lube

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010.
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	Supplemental information added.
Revision date	28/10/2015
Revision	2
SDS number	12394
SDS status	Approved.
Risk phrases in full	R11 Highly flammable. R12 Extremely flammable. R38 Irritating to skin. R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R62 Possible risk of impaired fertility. R65 Harmful: may cause lung damage if swallowed. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

The attached supplier's/distributor's Safety Data Sheet (SDS) is made available for internal reference use only; it is not to be redistributed outside of your organisation without the express permission of the supplier or distributor. The attached SDS remains the intellectual property of, and all rights are reserved to the original compilers. Alcumus Sypol Limited makes no warranty either expressed or implied as to the suitability or accuracy of the attached SDS; it is the latest version of the SDS as made available to Alcumus Sypol Limited and may not always reflect the latest version(s) available direct from the supplier or distributor of the material described within the SDS. The use of any information within the attached SDS is at the sole discretion, risk and responsibility of yourselves as subscribers to the Sypol CMS database. No representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by Alcumus Sypol Limited or by its officers, employees or agents in relation to the adequacy, accuracy, completeness or reasonableness of the attached SDS. All and any such responsibility and liability is expressly disclaimed to the extent permitted by law. While Alcumus Sypol Limited used the information within the attached SDS to compile the associated assessment, the classification used by Alcumus Sypol Limited to compile the assessment may differ from the classification assigned to the supplier or distributor if it is appropriate to do so under the classification requirements of any relevant domestic or international law to which the supplier or distributor is subject.